


# ADHTAPES LTD

Tel: +86-0755-2301-3413 | Web: [www.adhtapes.com](http://www.adhtapes.com) | Email: [info@adhtapes.com](mailto:info@adhtapes.com)

## Technical Data Sheet

PET masking tape is made of the polyester film as the backing and coated with silicone adhesive one side.



Silicone Adhesive  
Polyester Film

| PROPERTIES             | UNIT   | VALUE                    |
|------------------------|--------|--------------------------|
| Item No.               | /      | S02-6080                 |
| Adhesive               | /      | Silicone                 |
| Carrier                | /      | PET                      |
| Color                  | /      | Green                    |
| Backing Thickness      | mm     | 0.06                     |
| Total thickness        | mm     | 0.08±0.005               |
| Release Liner          | /      | No                       |
| Standard Roll Width    | mm     | 1070                     |
| Standard Roll Length   | m      | 33   50   66   100   500 |
| Withstand voltage      | KV     | ≥6                       |
| Tensile Strength       | N/25mm | ≥230                     |
| Breakage Elongation    | %      | ≥60                      |
| Peel Adhesion          | N/25mm | 11±1                     |
| Temperature Resistance |        |                          |
| Short term             | ℃      | ≥ 200                    |
| Long term              | ℃      | ≥ 180                    |
| Shelf life             | Month  | 12                       |

The data in this data table are the measured values of the product under certain conditions and are not guaranteed values.

### Application:

- Powder coating.
- Painting.
- High-temperature shielding.